Mr. Frank Pohlmann KUS Zollner Division 2425 South Coliseum Boulevard Fort Wayne, Indiana 46803

Dear Mr. Pohlmann:

Re: Exempt Construction and Operation Status, 003-12315-00064

The application from KUS Zollner Division, received on May 30, 2000, has been reviewed. Based on the data submitted and the provisions in 326 IAC 2-1.1-3, it has been determined that the following modification to the existing melt furnace #1 (ID M1), located at 2425 South Coliseum Boulevard, Fort Wayne, Indiana, is classified as exempt from air pollution permit requirements:

(a) One (1) melt furnace, identified as M1, with a maximum melt capacity of 1,200 pounds per hour, equipped with one (1) natural gas-fired melt burner, with a maximum heat input capacity of 2.0 million British thermal units (MMBtu) per hour, and two (2) natural gas-fired flat flame holding burners, each with a maximum heat input capacity of 1.0 MMBtu per hour.

Note: The above listed melt furnace was previously permitted in a Federally Enforceable State Operating Permit (FESOP) (F003-5869-00064) issued to this source on December 9, 1996, as an electric melt furnace with a maximum melt capacity of 800 pounds per hour. This unit is exempt because potential emissions are all under the exemption levels specified in 326 IAC 2-1.1-3(d)(1) (Exemptions). This modification does not affect any of the State or Federal permitting rules.

The following conditions shall be applicable:

- (1) Pursuant to 326 IAC 5-1-2 (Opacity Limitations) except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following:
  - (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
  - (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of 15 minutes (60 readings) in a 6-hour period as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuos opacity monitor in a six (6) hour period.
- Pursuant to 326 IAC 6-3-2 (Process Operations), the PM emissions from the melt furnace, identified as M1, shall not exceed the allowable emission rate of 2.91 pounds per hour, based on a process weight rate of 1,200 pounds per hour. This emission limit was calculated using the following:

Interpolation and extrapolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

 $E = 4.10 P^{0.67}$  where E = rate of emission in pounds per hour and P = process weight rate in tons per hour

KUS Zollner Division Fort Wayne, Indiana Permit Reviewer: TE/EVP Page 2 of 2 Exemption No. 003-12315-00064

This existing source has been issued a FESOP (F-003-5869-00064) on December 9, 1996. This source has submitted an application for a FESOP modification to incorporate the above mentioned modification on December 21, 1999.

An application or notification shall be submitted in accordance with 326 IAC 2 to the Office of Air Management (OAM) if the source proposes to construct new emission units, modify existing emission units, or otherwise modify the source.

Sincerely,

Paul Dubenetzky, Chief Permits Branch Office of Air Management

### TE/EVP

cc: File - Allen County

Allen County Health Department Air Compliance - Jennifer Schick Permit Tracking - Janet Mobley Air Programs Section- Michelle Boner

# Appendix A: Emission Calculations Source Emissions Summary After Modification

Company Name: KUS Zollner Division

Address City IN Zip: 2425 South Coliseum Blvd., Fort Wayne, Indiana 46803

**Exemption No.:** 003-12315 **PIt ID:** 003-00064

**Reviewer:** Trish Earls/EVP **Date:** May 30, 2000

## **Total Potential To Emit (tons/year)**

		Emissions Generating Activity			
Pollutant	Melt Furnace #1	Pouring/Casting Emissions	Natural Gas Combustion	TOTAL	
PM	0.05	0.00	0.03	0.0	
PM10	0.34	0.00	0.13	0.4	
SO2	0.00	0.05	0.01	0.00	
NOx	0.00	0.03	1.75	1.78	
VOC	0.00	0.37	0.10	0.4	
CO	0.00	0.00	1.47	1.4	
total HAPs***	0.00	0.00	0.03	0.03	
worst case single HAP***	0.00	0.00	0.03	0.0	

Total emissions based on rated capacities at 8,760 hours/year.

#### Appendix A: Secondary Metal Production Aluminum Potential Emissions from Modified Equipment

Company Name: KUS Zollner Division

Address City IN Zip: 2425 South Coliseum Blvd., Fort Wayne, Indiana 46803 Exemption No.: 003-12315

emption No.: 003-12315
PIt ID: 003-00064
Reviewer: Trish Earls/EVP
Date: May 30, 2000

SCC# 3-04-001-03 Smelting Furnace/Reverberatory Melt Furnace #1		Theoryphore				
TYPE OF MATERIAL		Throughput LBS/HR	1 TON/2000 lbs	TON/HR		
Aluminum	]	1200	2000	0.6		
	PM ** Ibs/ton Produced 0.019	PM10 ** Ibs/ton Produced 0.13	SOx Ibs/ton Produced 0	NOx Ibs/ton Produced 0	VOC Ibs/ton Produced 0	CO lbs/tons Produced 
Potential Emissions lbs/hr	0.01	0.08	0.0	0.0	0.0	
Potential Emissions lbs/day	0.27	1.87	0.0	0.0	0.0	
Potential Emissions tons/year	0.05	0.34	0.0	0.0	0.0	
SCC# 3-04-001-04						
Fluxing/Chlorine  TYPE OF MATERIAL		Throughput LBS/HR	1 TON/2000 lbs	TON/HR		
Flux	]	0	2000	0		
	PM *	PM10 *	SOx	NOx	voc	со
	lbs/ton Chlorine	lbs/ton Chlorine	lbs/ton Chlorine	lbs/ton Chlorine	lbs/ton Chlorine	lbs/tons Chlorine
	1000	532	0.00	0.00	0.00	
Potential Emissions Ibs/hr	0.0	0.0	0.0	0.0	0.0	
Potential Emissions lbs/day	0.0	0.0	0.0	0.0	0.0	
Potential Emissions tons/year	0.0	0.0	0.0	0.0	0.0	0
SCC# 3-04-001-14						
Pouring/Casting						
TYPE OF MATERIAL		Throughput LBS/HR	1 TON/2000 lbs	TON/HR		
	1		1 TON/2000 lbs	TON/HR 0.6		
TYPE OF MATERIAL	PM Ibs/ton metal charged 	LBS/HR			VOC * Ibs/ton metal charged 0.14	CO Ibs/tons metal charged 
TYPE OF MATERIAL	lbs/ton metal charged	LBS/HR 1200 PM10 Ibs/ton metal charged	2000 SOx * Ibs/ton metal charged	0.6  NOx *  Ibs/ton metal charged	lbs/ton metal charged	lbs/tons metal charged
TYPE OF MATERIAL  Aluminum	lbs/ton metal charged	LBS/HR  1200  PM10  Ibs/ton metal charged	2000 SOx * Ibs/ton metal charged 0.02	0.6  NOx *  Ibs/ton metal charged 0.01	lbs/ton metal charged 0.14	lbs/tons metal charged

<sup>\*</sup> Note: Emission factor is from FIRE version 6.01.

alum.wk4 7/95

<sup>\*\*</sup>Note: PM and PM-10 emission factors for melt furnace were based on approved stack test results from a stack test performed January 18, 2000 on furnace #14. PM-10 includes filterable and condensible particulate matter.

#### Appendix A: Emissions Calculations Emissions From Natural Gas Combustion MM BTU/HR <100

Company Name: KUS Zollner Division

Address City IN Zip: 2425 South Coliseum Blvd., Fort Wayne, Indiana 46803

 Exemption No.:
 003-12315

 Plt ID:
 003-00064

 Reviewer:
 Trish Earls/EVP

 Date:
 May 30, 2000

Heat Input Capacity Potential Throughput

MMBtu/hr MMCF/yr

4.0 35.0

#### Pollutant

		Foliulani				
	PM*	PM10*	SO2	NOx	VOC	СО
Emission Factor in lb/MMCF	1.9	7.6	0.6	100.0	5.5	84.0
				**see below		
Potential Emission in tons/yr	0.03	0.13	0.01	1.75	0.10	1.47

<sup>\*</sup>PM emission factor is filterable PM only. PM10 emission factor is filterable and condensable PM10 combined.

#### Methodology

All emission factors are based on normal firing.

MMBtu = 1,000,000 Btu

MMCF = 1,000,000 Cubic Feet of Gas

Potential Throughput (MMCF) = Heat Input Capacity (MMBtu/hr) x 8,760 hrs/yr x 1 MMCF/1,000 MMBtu

Emission Factors are from AP 42, Chapter 1.4, Tables 1.4-1, 1.4-2, 1.4-3, SCC #1-02-006-02, 1-01-006-02, 1-03-006-02, and 1-03-006-03 (SUPPLEMENT D 3/98)

Emission (tons/yr) = Throughput (MMCF/yr) x Emission Factor (lb/MMCF)/2,000 lb/ton

HAPs - Organics

Emission Factor in lb/MMcf	Benzene 2.1E-03	Dichlorobenze ne 1.2E-03	Formaldehyde 7.5E-02	Hexane 1.8E+00	Toluene 3.4E-03
Potential Emission in tons/yr	3.7E-05	2.1E-05	1.3E-03	3.2E-02	6.0E-05

#### HAPs - Metals

		HAPS - IVIELAIS				
Emission Factor in lb/MMcf	Lead 5.0E-04	Cadmium 1.1E-03	Chromium 1.4E-03	Manganese 3.8E-04	Nickel 2.1E-03	Total
Potential Emission in tons/yr	8.8E-06	1.9E-05	2.5E-05	6.7E-06	3.7E-05	0.03

Methodology is the same as listed above.

The five highest organic and metal HAPs emission factors are provided above. Additional HAPs emission factors are available in AP-42, Chapter 1.4.

<sup>\*\*</sup>Emission Factors for NOx: Uncontrolled = 100, Low NOx Burner = 50, Low NOx Burners/Flue gas recirculation = 32